

SIMATIC ET 200SP PS/1AC/24VDC/5A

SIMATIC ET 200SP PS 24V/5A Stabilized power supply Input: 120/230 V
AC Output: 24 V DC/5 A



| Input | |
|--|---|
| Input | 1-phase AC |
| • Note | Automatic range selection |
| supply voltage | |
| • 1 at AC rated value | 120 V |
| • 2 at AC rated value | 230 V |
| input voltage | |
| • 1 at AC | 85 ... 132 V |
| • 2 at AC | 170 ... 264 V |
| Wide-range input | No |
| Overvoltage resistance | 2.3 × Vin rated, 1.3 ms |
| Mains buffering | at Vin = 93/187 V |
| Mains buffering at Iout rated, min. | 20 ms; at Vin = 93/187 V |
| Rated line frequency 1 | 50 Hz |
| Rated line frequency 2 | 60 Hz |
| Rated line range | 47 ... 63 Hz |
| input current | |
| • at rated input voltage 120 V | 2.16 A |
| • at rated input voltage 230 V | 1.22 A |
| Switch-on current limiting (+25 °C), max. | 45 A |
| I ² t, max. | 3.15 A ² ·s |
| Built-in incoming fuse | T 3,15 A/250 V (not accessible) |
| Protection in the mains power input (IEC 898) | recommended LS switch: B/C 6 A/3 A |
| Output | |
| Output | Controlled, isolated DC voltage |
| Rated voltage Vout DC | 24 V |
| • output voltage at output 1 at DC rated value | 24 V |
| Total tolerance, static ± | 3 % |
| Static mains compensation, approx. | 0.1 % |
| Static load balancing, approx. | 1 % |
| Residual ripple peak-peak, max. | 150 mV |
| Residual ripple peak-peak, typ. | 50 mV |
| Spikes peak-peak, max. (bandwidth: 20 MHz) | 240 mV |
| Spikes peak-peak, typ. (bandwidth: 20 MHz) | 150 mV |
| Adjustment range | 22.8 ... 28 V |
| product function output voltage adjustable | Yes |
| Output voltage setting | via potentiometer |
| Status display | Green LED for 24 V OK |
| Signaling | Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK" |

| | |
|---|--|
| On/off behavior | Overshoot of Vout < 3 % |
| Startup delay, max. | 0.3 s |
| Voltage rise, typ. | 30 ms |
| Rated current value Iout rated | 5 A |
| Current range | 0 ... 6 A |
| • Note | 5 A up to +60°C; +60 ... +70 °C: Derating 3%/K |
| supplied active power typical | 120 W |
| short-term overload current | |
| • on short-circuiting during the start-up typical | 15 A |
| • at short-circuit during operation typical | 15 A |
| duration of overloading capability for excess current | |
| • on short-circuiting during the start-up | 800 ms |
| • at short-circuit during operation | 800 ms |
| Parallel switching for enhanced performance | Yes |
| Numbers of parallel switchable units for enhanced performance | 2 |
| Efficiency | |
| Efficiency at Vout rated, Iout rated, approx. | 88 % |
| Power loss at Vout rated, Iout rated, approx. | 17 W |
| power loss [W] during no-load operation maximum | 2.7 W |
| Closed-loop control | |
| Dynamic mains compensation (Vin rated ±15 %), max. | 0.3 % |
| Dynamic load smoothing (Iout: 10/90/10 %), Uout ± typ. | 3 % |
| Load step setting time 10 to 90%, typ. | 1 ms |
| Load step setting time 90 to 10%, typ. | 1 ms |
| Protection and monitoring | |
| Output overvoltage protection | protection against overvoltage in case of internal fault Vout < 31.8 V |
| Current limitation | 7 ... 7.5 A |
| property of the output short-circuit proof | Yes |
| Short-circuit protection | Constant current characteristic |
| enduring short circuit current RMS value | |
| • typical | 7 A |
| overcurrent overload capability in normal operation | overload capability 150 % Iout rated up to 5 s/min |
| Overload/short-circuit indicator | - |
| Safety | |
| Primary/secondary isolation | Yes |
| galvanic isolation | Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178 |
| Protection class | Class I |
| leakage current | |
| • maximum | 3.5 mA |
| • typical | 1 mA |
| Degree of protection (EN 60529) | IP20 |
| Approvals | |
| CE mark | Yes |
| UL/cUL (CSA) approval | cULus-Listed (UL61010-2-201, CSA C22.2 No.142), cCSAus (CSA C22.2 No. 60950-1, UL 60950-1) |
| certificate of suitability ATEX | Yes; ATEX (EX) II 3G Ex ec nC IIC T3 Gc |
| Explosion protection | IECEX Ex ec nC IIC T3 Gc; ATEX (EX) II 3G Ex ec nC IIC T3 Gc |
| certificate of suitability IECEx | Yes; IECEx Ex ec nC IIC T3 Gc |
| certificate of suitability NEC Class 2 | No |
| CB approval | Yes |
| certificate of suitability EAC approval | Yes |
| Marine approval | BV, DNV GL |
| EMC | |
| Emitted interference | EN 61000-6-3 Class B |
| Supply harmonics limitation | EN 61000-3-2 |
| Noise immunity | EN 61000-6-2 |
| environmental conditions | |
| ambient temperature | |
| • during operation | -30 ... +70 °C |

| | |
|--|---|
| — Note | with natural convection |
| • during transport | -40 ... +85 °C |
| • during storage | -40 ... +85 °C |
| Humidity class according to EN 60721 | Climate class 3K3, 5 ... 95% no condensation |
| Mechanics | |
| Connection technology | Push-in terminals |
| Connections | |
| • Supply input | L, N, PE: 1 push-in terminal each for 0.2 ... 2.5 mm ² single-core/finely stranded |
| • Output | +, -: 2 push-in terminals each for 0.2 ... 2.5 mm ² |
| • Auxiliary | Signaling contact: 2 push-in terminals for 0.2 ... 2.5 mm ² |
| • signaling contact | 2 push-in terminals for 0.2 ... 2.5 mm ² |
| product function | |
| • removable terminal at input | Yes |
| • removable terminal at output | Yes |
| width of the enclosure | 160 mm |
| height of the enclosure | 117 mm |
| depth of the enclosure | 74 mm |
| required spacing | |
| • top | 50 mm |
| • bottom | 50 mm |
| • left | 0 mm |
| • right | 0 mm |
| Weight, approx. | 0.5 kg |
| product feature of the enclosure housing can be lined up | Yes |
| Installation | Snaps onto DIN rail EN 60715 35x7.5/15 |
| electrical accessories | Redundancy module, buffer module, selectivity module, DC UPS |
| MTBF at 40 °C | 1 598 441 h |
| other information | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |

