

SIMATIC DP, 1 ELECTRON. MODULE ET 200S: 4DI DC 24V NAMUR, 15 MM WIDTH, WITH LED SF (GROUP FAULT),



| Supply voltage | |
|---|--------------------|
| Rated value (DC) | |
| <ul style="list-style-type: none"> • 24 V DC | Yes |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Encoder supply | |
| Number of outputs | 1 |
| Type of output voltage | min. 8.2 V, loaded |
| Short-circuit protection | Yes; Electronic |
| Output current | |
| <ul style="list-style-type: none"> • Rated value | 45 mA |
| Power loss | |
| Power loss, typ. | 1.6 W |
| Address area | |
| Address space per module | |
| <ul style="list-style-type: none"> • with packing | 4 bit |
| <ul style="list-style-type: none"> • without packing | 1 byte |

| Digital inputs | |
|--|-----------------------|
| Number of digital inputs | 4 |
| Number of NAMUR inputs | 4 |
| Parallel switching of inputs | No |
| Number of simultaneously controllable inputs | |
| • Number of simultaneously controllable inputs | 4 |
| Input voltage | |
| • Type of input voltage | DC |
| Input current | |
| for 10 k switched contact | |
| — for signal "0" | 0.35 to 1.2 mA |
| — for signal "1" | 2.1 to 7 mA |
| for unswitched contact | |
| — for signal "0", max. (permissible quiescent current) | 0.5 mA |
| — for signal "1" | typ. 8 mA |
| for NAMUR encoders | |
| — for signal "0" | 0.35 to 1.2 mA |
| — for signal "1" | 2.1 to 7 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — at "0" to "1", max. | 4.6 μ s |
| — at "1" to "0", max. | 4.6 μ s |
| Cable length | |
| • shielded, max. | 200 m |
| Interrupts/diagnostics/status information | |
| Diagnostic functions | Yes; Diagnostic alarm |
| Alarms | |
| • Diagnostic alarm | Yes; can be set |
| • Hardware interrupt | No |
| Diagnostic messages | |
| • Diagnostic information readable | Yes |
| • Wire-break | Yes |
| Diagnostics indication LED | |
| • Group error SF (red) | Yes |
| • Status indicator digital input (green) | Yes; per channel |
| Parameter | |
| Remark | 12 byte |
| Potential separation | |
| Potential separation digital inputs | |
| • between the channels | No |

- between the channels and backplane bus
- Between the channels and load voltage L+

Yes

Yes

Permissible potential difference

between different circuits

75 V DC/60 V AC

Isolation

Isolation tested with

500 V DC

Dimensions

Width

15 mm

Height

81 mm

Depth

52 mm

Weights

Weight, approx.

35 g

last modified:

14.05.2016