

SIMATIC DP, ELECTRON. MODULE ET200S: 2DO RELAY(FORM C CONT.) DC24V-48V/5A, AC24V-230V/5A, 15 MM WIDTH, FIRST-UP SIGNAL, WITH MANUAL ACTUATION



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• with packing	2 bit
• without packing	1 byte
Digital outputs	
Number of digital outputs	2
Short-circuit protection	No
Limitation of inductive shutdown voltage to	No

Controlling a digital input	Yes
<b>Output current</b>	
• for signal "1" rated value	5 A
• for signal "1" minimum load current	8 mA
<b>Switching frequency</b>	
• with resistive load, max.	2 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	2 Hz
<b>Relay outputs</b>	
<b>Switching capacity of contacts</b>	
— Thermal continuous current, max.	5 A
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	No
<b>Interrupts/diagnostics/status information</b>	
Diagnostic functions	No
Substitute values connectable	Yes; 0/1
<b>Diagnostics indication LED</b>	
• Status indicator digital output (green)	Yes
<b>Parameter</b>	
Behavior on CPU/Master STOP	Substitute a value/keep last value
<b>Potential separation</b>	
<b>Potential separation digital outputs</b>	
• between the channels	Yes
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
<b>Isolation</b>	
<b>tested with</b>	
• Channels against backplane bus and load voltage L+	1500 V AC
• Load voltage L+ against backplane bus	500 V DC
<b>Ambient conditions</b>	
<b>Extended ambient conditions</b>	
• relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)

## Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

## Weights

Weight, approx.	50 g
-----------------	------

**last modified:** 14.05.2016