

SIMATIC DP, ELECTRONIC MODULE FOR ET 200S, 2 AI STAND.
 I-2DMU 15 MM WIDE, 4 .. 20MA; 13 BIT FOR 2-WIRE
 TRANSDUCER CYCLE TIME 65 MS/CHANNEL WITH LED SF
 (GROUP FAULT)



Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) Reverse polarity protection 	24 V; From power module Yes; Destruction limit 35 mA per channel
Input current	
from load voltage L+ (without load), max.	80 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> Address space per module, max. 	4 byte
Analog inputs	
Number of analog inputs	2
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	Number of active channels per module x basic conversion time

Input ranges	
• Voltage	No
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), currents	
• 4 mA to 20 mA	Yes; on 50 ohms
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	13 bit; 4 to 20 mA: 13 bits
• Integration time (ms)	16,7 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
• Conversion time (per channel)	65 ms; 55 / 65 ms
Smoothing of measured values	
• parameterizable	Yes; In four stages by means of digital filtering
• Step: None	Yes; 1 x cycle time
• Step: low	Yes; 4 x cycle time
• Step: Medium	Yes; 32 x cycle time
• Step: High	Yes; 64 x cycle time
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max.	750 Ω
Errors/accuracies	
Linearity error (relative to full-scale), (+/-)	0.01 %
Temperature error (relative to full-scale), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to full-scale), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Current, relative to full-scale, (+/-)	0.6 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to full-scale, (+/-)	0.4 %
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, $f1 =$ interference frequency	

- Series mode interference (peak value of interference < rated value of input range), min. 70 dB

Isochronous mode

Isochronous operation (application synchronized up to terminal) No

Interrupts/diagnostics/status information

Diagnostic messages

- Wire-break Yes
- Group error Yes
- Overflow/underflow Yes

Diagnostics indication LED

- Group error SF (red) Yes

Parameter

Remark 4 byte
 Measurement type/range deactivated / 4 to 20 mA
 Group diagnostics Disable / enable
 Overflow/underflow Disable / enable

Potential separation

Potential separation analog inputs

- between the channels No
- between the channels and backplane bus Yes
- Between the channels and load voltage L+ No

Isolation

Isolation tested with 500 V DC

Dimensions

Width 15 mm
 Height 81 mm
 Depth 52 mm

Weights

Weight, approx. 40 g

last modified: 14.05.2016