

SIMATIC DP, ELECTRONIC MODULE FOR ET 200S, 2 AI STAND. I-4DMU 15 MM WIDE, +/-20MA; 13 BIT + SIGN, 4 .. 20MA; 12 BIT FOR 4-WIRE TRANSDUCER CYCLE TIME 65 MS/CHANNEL WITH LED SF (GROUP FAULT)



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; From power module
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	Number of active channels per module x basic conversion time
Input ranges	

• Voltage	No
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), currents	
• -20 mA to +20 mA	Yes; 50 Ohm
• 4 mA to 20 mA	Yes; 50 Ohm
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit; +/-20 mA: 14 bits, 4 to 20 mA: 13 bits
• Integration time (ms)	16,7 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
• Conversion time (per channel)	65 ms; 55 / 65 ms
Smoothing of measured values	
• parameterizable	Yes; In four stages by means of digital filtering
• Step: None	Yes; 1 x cycle time
• Step: low	Yes; 4 x cycle time
• Step: Medium	Yes; 32 x cycle time
• Step: High	Yes; 64 x cycle time
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max.	750 Ω
Errors/accuracies	
Linearity error (relative to full-scale), (+/-)	0.01 %
Temperature error (relative to full-scale), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to full-scale), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Current, relative to full-scale, (+/-)	0.6 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to full-scale, (+/-)	0.4 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency	

- Series mode interference (peak value of interference < rated value of input range), min.

70 dB

Isochronous mode

Isochronous operation (application synchronized up to terminal)

No

Interrupts/diagnostics/status information

Diagnostic messages

- Wire-break
- Group error
- Overflow/underflow

Yes; Measuring range 4 to 20 mA only

Yes

Yes

Diagnostics indication LED

- Group error SF (red)

Yes

Parameter

Remark

4 byte

Diagnostics wire break

Disable / enable (only in measuring range 4 to 20 mA)

Measurement type/range

deactivated / +/-20 mA / 4 to 20 mA

Group diagnostics

Disable / enable

Overflow/underflow

Disable / enable

Potential separation

Potential separation analog inputs

- between the channels
- between the channels and backplane bus
- Between the channels and load voltage L+

No

Yes

No

Isolation

Isolation tested with

500 V DC

Dimensions

Width

15 mm

Height

81 mm

Depth

52 mm

Weights

Weight, approx.

40 g

last modified:

14.05.2016