

SIMATIC ET 200SP, ANALOG INPUT MODULE, AI 8xRTD/TC 2-WIRE HIGH FEATURE PACKING UNIT: 10 PIECES, FITS TO BU-TYPE A0, A1, COLOR CODE CC00, CHANNEL DIAGNOSIS, 16BIT, +/-0,1%



| General information | |
|---|---|
| Product type designation | ET 200SP, AI 8xRTD/TC 2-wire HF, VPE 10 |
| Firmware version | V2.0 |
| <ul style="list-style-type: none"> FW update possible | Yes |
| usable BaseUnits | BU type A0, A1 |
| Color code for module-specific color identification plate | CC00 |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version | V13 |
| <ul style="list-style-type: none"> STEP 7 configurable/integrated as of version | V5.5 / - |
| <ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision | GSD Revision 5 |
| <ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision | GSDML V2.3 |
| Operating mode | |
| <ul style="list-style-type: none"> Oversampling | No |
| <ul style="list-style-type: none"> MSI | No |

CiR - Configuration in RUN

| | |
|------------------------------------|-----|
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN | Yes |

Supply voltage

| | |
|-------------------------------------|--------|
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |

Input current

| | |
|---------------------------|-------|
| Current consumption, max. | 35 mA |
|---------------------------|-------|

Power loss

| | |
|------------------|--------|
| Power loss, typ. | 0.75 W |
|------------------|--------|

Address area

| | |
|----------------------------------|--------------------------------------|
| Address space per module | |
| • Address space per module, max. | 16 byte; + 1 byte for QI information |

Analog inputs

| | |
|---|--|
| Number of analog inputs | 8 |
| permissible input voltage for voltage input (destruction limit), max. | 30 V |
| Constant measurement current for resistance-type transmitter, typ. | 2 mA |
| Cycle time (all channels), min. | Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels) |
| Technical unit for temperature measurement adjustable | Yes; °C/°F/K |

Input ranges (rated values), voltages

| | |
|---|------------------------|
| • -1 V to +1 V | Yes; 16 bit incl. sign |
| • Input resistance (-1 V to +1 V) | 1 MΩ |
| • -250 mV to +250 mV | Yes; 16 bit incl. sign |
| • Input resistance (-250 mV to +250 mV) | 1 MΩ |
| • -50 mV to +50 mV | Yes; 16 bit incl. sign |
| • Input resistance (-50 mV to +50 mV) | 1 MΩ |
| • -80 mV to +80 mV | Yes; 16 bit incl. sign |
| • Input resistance (-80 mV to +80 mV) | 1 MΩ |

Input ranges (rated values), thermocouples

| | |
|-----------------------------|------------------------|
| • Type B | Yes; 16 bit incl. sign |
| • Input resistance (Type B) | 1 MΩ |
| • Type C | Yes; 16 bit incl. sign |
| • Input resistance (Type C) | 1 MΩ |
| • Type E | Yes; 16 bit incl. sign |
| • Input resistance (Type E) | 1 MΩ |

- Type J
- Input resistance (type J)
- Type K
- Input resistance (Type K)
- Type L
- Input resistance (Type L)
- Type N
- Input resistance (Type N)
- Type R
- Input resistance (Type R)
- Type S
- Input resistance (Type S)
- Type T
- Input resistance (Type T)
- Type U
- Input resistance (Type U)
- Type TXK/TXK(L) to GOST
- Input resistance (Type TXK/TXK(L) to GOST)

Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ

Input ranges (rated values), resistance thermometer

- Ni 100
- Input resistance (Ni 100)
- Ni 1000
- Input resistance (Ni 1000)
- LG-Ni 1000
- Input resistance (LG-Ni 1000)
- Ni 120
- Input resistance (Ni 120)
- Ni 200
- Input resistance (Ni 200)
- Ni 500
- Input resistance (Ni 500)
- Pt 100
- Input resistance (Pt 100)
- Pt 1000
- Input resistance (Pt 1000)
- Pt 200
- Input resistance (Pt 200)
- Pt 500
- Input resistance (Pt 500)

Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ

Input ranges (rated values), resistors

- 0 to 150 ohms

Yes; 15 bit

| | |
|-------------------------------------|-------------|
| • Input resistance (0 to 150 ohms) | 1 MΩ |
| • 0 to 300 ohms | Yes; 15 bit |
| • Input resistance (0 to 300 ohms) | 1 MΩ |
| • 0 to 600 ohms | Yes; 15 bit |
| • Input resistance (0 to 600 ohms) | 1 MΩ |
| • 0 to 3000 ohms | Yes; 15 bit |
| • Input resistance (0 to 3000 ohms) | 1 MΩ |
| • 0 to 6000 ohms | Yes; 15 bit |
| • Input resistance (0 to 6000 ohms) | 1 MΩ |
| • PTC | Yes; 15 bit |
| • Input resistance (PTC) | 1 MΩ |

Thermocouple (TC)

| | |
|--------------------------------------|----------------------------|
| Temperature compensation | |
| — parameterizable | Yes |
| — Reference channel of the module | Yes |
| — internal comparison point | Yes; with BaseUnit type A1 |
| — Reference channel of the group | Yes |
| — Number of reference channel groups | 4; Group 0 to 3 |
| — fixed reference temperature | Yes |

Cable length

| | |
|------------------|--------------------------------|
| • shielded, max. | 200 m; 50 m with thermocouples |
|------------------|--------------------------------|

Analog value generation for the inputs

| | |
|-----------------------|---------------------------|
| Measurement principle | integrating (Sigma-Delta) |
|-----------------------|---------------------------|

Integration and conversion time/resolution per channel

| | |
|--|--|
| • Resolution with overrange (bit including sign), max. | 16 bit |
| • Integration time, parameterizable | Yes |
| • Basic conversion time, including integration time (ms) | |
| — additional processing time for wire-break check | 2 ms; In the ranges resistance thermometers, resistors and thermocouples |
| • Interference voltage suppression for interference frequency f1 in Hz | 16.6 / 50 / 60 Hz |
| • Conversion time (per channel) | 180 / 60 / 50 ms |

Smoothing of measured values

| | |
|--------------------|-----------------------|
| • Number of levels | 4; None; 4/8/16 times |
| • parameterizable | Yes |

Encoder

Connection of signal encoders

| | |
|---|-----|
| • for voltage measurement | Yes |
| • for resistance measurement with two-wire connection | Yes |

- for resistance measurement with three-wire connection
- for resistance measurement with four-wire connection

No

No

Errors/accuracies

| | |
|--|--|
| Linearity error (relative to full-scale), (+/-) | 0.01 %; +/- 0.1 % for resistance thermometers and resistance |
| Temperature error (relative to full-scale), (+/-) | 0.0009 %/K; +/- 0.005 %/K at thermocouple |
| Crosstalk between the inputs, min. | -50 dB |
| Repeat accuracy in steady state at 25 °C (relative to full-scale), (+/-) | 0.05 % |

Operational error limit in overall temperature range

- Voltage, relative to full-scale, (+/-) 0.1 %
- Resistance, relative to full-scale, (+/-) 0.1 %

Basic error limit (operational limit at 25 °C)

- Voltage, relative to full-scale, (+/-) 0.05 %
- Resistance, relative to full-scale, (+/-) 0.05 %

Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency

- Series mode interference (peak value of interference < rated value of input range), min. 70 dB
- Common mode voltage, max. 10 V
- Common mode interference, min. 90 dB

Isochronous mode

Isochronous operation (application synchronized up to terminal)

No

Interrupts/diagnostics/status information

Diagnostics Yes

Alarms

- Diagnostic alarm Yes
- Limit value alarm Yes; two upper and two lower limit values in each case

Diagnostic messages

- Monitoring the supply voltage Yes
- Wire-break Yes; channel by channel
- Group error Yes
- Overflow/underflow Yes; channel by channel

Diagnostics indication LED

- Monitoring of the supply voltage (PWR-LED) Yes; green PWR LED
- Channel status display Yes; Green LED
- for channel diagnostics Yes; Red LED
- for module diagnostics Yes; green/red DIAG LED

Potential separation

Potential separation channels

- between the channels
- between the channels and backplane bus
- between the channels and the power supply of the electronics

No
Yes
Yes

Permissible potential difference

| | |
|----------------------------|----------------------------------|
| between different circuits | 75 V DC/60 V AC (base isolation) |
| between the inputs (UCM) | 10 V DC |

Isolation

| | |
|-----------------------|----------------------|
| Isolation tested with | 707 V DC (type test) |
|-----------------------|----------------------|

Dimensions

| | |
|-------|-------|
| Width | 15 mm |
|-------|-------|

Weights

| | |
|-----------------|------|
| Weight, approx. | 32 g |
|-----------------|------|

last modified: 14.05.2016