

SIMATIC DP, ELECTRONIC MODULE FOR ET 200S, 2 AO I HIGH SPEED 15 MM WIDE, +/-20 MA; 16 BIT, 4 . .20 MA; 16 BIT CYCLE TIME 0.1 MS WITH LED SF (GROUP FAULT)



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	150 mA; With load
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	2.4 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog outputs	
Number of analog outputs	2
Current output, no-load voltage, max.	18 V
Cycle time (all channels) max.	250 μs
Output ranges, current	

• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for current output two-wire connection	Yes
• for current output four-wire connection	No
Load impedance (in rated range of output)	
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	1 mH; for TWA 100µs
Destruction limits against externally applied voltages and currents	
• Voltages at the outputs towards MANA	15 V; Max. 15 V / 5 hours (higher voltages not permissible even briefly)
• Current, max.	30 mA; DC
Cable length	
• shielded, max.	200 m; Max. 20 m for TWA 100 µs
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
Settling time	
• for resistive load	0.05 ms
• for capacitive load	0.05 ms; at a load of up to 500 ohms/100 nF and a max. cable length of 20 m
• for inductive load	0.05 ms
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.03 %; with resistive load
Temperature error (relative to output range), (+/-)	0.01 %/K
Crosstalk between the outputs, min.	-60 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.03 %
Operational error limit in overall temperature range	
• Current, relative to output range, (+/-)	0.2 %; Specified value applies to loads from 200 to 350 Ohm, deviating operational limits for loads up to 200 Ohm and from 350 to 500 Ohm with up to 0.4%
Basic error limit (operational limit at 25 °C)	
• Current, relative to output range, (+/-)	0.1 %; Specified value applies for loads from 200 to 350 ohms, deviating basic error limits for loads up to 200 ohms and from 350 to 500 ohms with up to 0.3%
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Interrupts/diagnostics/status information	

Substitute values connectable	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Wire-break	Yes
• Group error	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes

Parameter	
Remark	7 byte
Diagnostics wire break	Disable / enable
Output type/range	deactivated / +/-20 mA / 4 to 20 mA
Group diagnostics	Disable / enable
Behavior on CPU/Master STOP	Output current and de-energized/substitute a value/keep last value

Potential separation	
Potential separation analog outputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes

Permissible potential difference	
between MANA and M internally (UISO)	75 V DC/60 V AC

Isolation	
Isolation tested with	500 V DC

Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm

Weights	
Weight, approx.	40 g

last modified: 20.05.2016