

SIMATIC DP, INTERFACE MODULE IM151-3 PN FO FOR ET 200S
 2 PROFINET FO INTERFACES INTEGRATED 2-PORT SWITCH
 MAX. OF 63 PERIPHERAL MODULES USABLE FOR PROFISAFE
 MODULES MAX. 2M STATION WIDTH INCL. TERMINATING
 MODULE



Figure similar

Configuration control	
via dataset	Yes
Supply voltage	
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Input current	
from supply voltage 1L+, max.	200 mA
Power loss	
Power loss, typ.	5 W
Address area	
Addressing volume	
• Inputs	256 byte
• Outputs	256 byte
Interfaces	
Number of PROFINET interfaces	1
Interface physics, FOC	Yes
PROFINET IO	

• Autocrossing	Yes
• automatic detection of transmission rate	Yes
• Transmission rate, max.	100 Mbit/s
• Services	Ping; arp; LLDP; network diagnostics (SNMP) / MIB-2, reset SNMP parameters to factory settings; prioritized startup; media redundancy MRP; shared device
• RJ 45	Yes

1. Interface

Functionality

• PROFINET IO Device	Yes
----------------------	-----

PROFINET IO Device

Services

— Isochronous mode	No
— IRT	Yes
— PROFINergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2

Protocols

Supports protocol for PROFINET IO	Yes
MRP	Yes

Interrupts/diagnostics/status information

Alarms	Yes
Diagnostic functions	Yes
Diagnostics indication LED	
• Bus fault BF (red)	Yes
• Group error SF (red)	Yes
• Monitoring 24 V voltage supply ON (green)	Yes
• Connection to network LINK (green)	Yes

Potential separation

between Ethernet and electronics	Yes
----------------------------------	-----

Permissible potential difference

between different circuits	75 V DC/60 V AC
----------------------------	-----------------

Standards, approvals, certificates

CE mark	Yes
UL approval	Yes

Ambient conditions

Ambient temperature during operation	
• min.	0 °C

• max.

60 °C

Dimensions

Width	60 mm
Height	119.5 mm
Depth	75 mm; with mounting rail

Weights

Weight, approx. 150 g

last modified: 14.05.2016