

SIMATIC ET 200MP PROFINET IO-DEVICE INTERFACEMODULE
 IM 155-5 PN FOR ET 200MP ELEKTRONIKMODULES; UP TO 12
 IO-MODULES SHARED DEVICE UP TO 2 IO-CONTROLLER; MRP;
 FW-UPDATE; I&M0...3;



General information	
Product type designation	IM 155-5 PN BA
HW functional status	FS01
Firmware version	V4.0.0
Vendor identification (VendorID)	0x002A
Device identifier (DeviceID)	0X0312
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V14 with HSP 0187
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 SP3 / -
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	V2.3 / -
Configuration control	
via user data	No
via dataset	No
Supply voltage	
Rated value (DC)	24 V

permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms

Input current	
Current consumption (rated value)	1 A
Current consumption, max.	1.7 A
Inrush current, max.	2.8 A
I^2t	0.04 A ² ·s

Power	
Infeed power to the backplane bus	14 W

Power loss	
Power loss, typ.	3 W

Address area	
Address space per module	
• Address space per module, max.	64 byte; per input / output
Address space per station	
• Address space per station, max.	64 byte; per input / output

Hardware configuration	
Integrated power supply	Yes
System power supply can be plugged in to left of IM	No
Number of permissible power segments	1
Rack	
• Modules per rack, max.	12; I/O modules
Submodules	
• Number of submodules per station, max.	108; 9 submodules / I/O modules

Interfaces	
Number of PROFINET interfaces	1; 2 ports (switch) RJ45

1. Interface	
Interface types	
• Number of ports	2
• integrated switch	Yes
• RJ 45 (Ethernet)	Yes
• BusAdapter (PROFINET)	No
Protocols	
• PROFINET IO Device	Yes
• Media redundancy	Yes

Interface types

RJ 45 (Ethernet)

• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• 100 Mbps	Yes
• Autonegotiation	Yes
• Autocrossing	Yes

Protocols

PROFINET IO Device

Services

— Isochronous mode	No
— Open IE communication	Yes
— IRT	No
— PROFINergy	No
— Prioritized startup	No
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2

Redundancy mode

• MRP	Yes
• MRPD	No
• PROFINET system redundancy (S2)	No

Open IE communication

• TCP/IP	Yes
• SNMP	Yes
• LLDP	Yes

Isochronous mode

Isochronous operation (application synchronized up to terminal)	No
Equidistance	No

Interrupts/diagnostics/status information

Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes

Diagnostics indication LED

• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• MAINT LED	Yes; yellow LED
• Connection display LINK TX/RX	Yes; 2x green-yellow LEDs

Potential separation

between backplane bus and electronics	No
between PROFINET and all other circuits	Yes

between supply and all other circuits	No
Permissible potential difference	
between different circuits	Safety extra low voltage SELV
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Network loading class	2
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. 	<ul style="list-style-type: none"> 0 °C 60 °C 0 °C 40 °C
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	236 g
last modified:	12/29/2018