SIEMENS

Data sheet

6GK1901-1BB20-2AB0

Product type designation

Product description

Suitability for use



IE FC RJ45 Plug 90 (2x2)

RJ45 data connector
IE FC RJ45 PLUG 90 2X2, RJ45 PLUG CONNECTOR
(10/100MBIT/S) WITH RUGGED METAL HOUSING AND FC
CONNECTING METHOD FOR IE FC CABLE 2X2 90 DGR CABLE
OUTLET 1 PACK = 10 PCS

For connection to IE FC TP cables 2x2, suitable for fast assembly

| · | with the FastConnect system | |
|--|---|--|
| Transmission rate | | |
| Transfer rate / for Industrial Ethernet | 10 Mbit/s, 100 Mbit/s | |
| Interfaces | | |
| Number of electrical connections | | |
| for Industrial Ethernet FC TP cables | 4 | |
| • for network components or terminal equipment | 1 | |
| Type of electrical connection | | |
| • for Industrial Ethernet FC TP cables | integrated cut-and-clamp contacts for 4-wire TP FC installation cable | |
| • for network components or terminal equipment | RJ45 connector | |
| Type of electrical connection / FastConnect | Yes | |
| Mechanical data | | |
| Material / of the enclosure | metal | |
| Number of reuses | 10 | |
| Locking mechanism design | other | |

| Design, dimensions and weight | |
|---------------------------------|------------------|
| Type of cable outlet | 90° cable outlet |
| Width | 13.7 mm |
| Height | 16 mm |
| Depth | 42 mm |
| Net weight | 35 g |
| Connectable cable cross-section | 6.5 6.5 mm |

| Permitted ambient conditions | | |
|--|------------|--|
| Ambient temperature | | |
| during operation | -40 +85 °C | |
| during storage | -40 +85 °C | |
| during transport | -40 +85 °C | |
| Relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % | |
| Protection class IP | IP20 | |

| Product properties, functions, components / general | | |
|---|-----|--|
| Product feature | | |
| PoE capability | Yes | |
| PoE+capability | Yes | |
| • silicon-free | Yes | |
| Product component | | |
| strain relief | Yes | |

| Certificate of suitability | |
|---|------|
| RoHS conformity | Yes |
| UL approval | Yes |
| • cULus approval | Yes |
| Railway application in accordance with EN 50155 | No |
| Standard for structured cabling | Cat5 |

Further Information / Internet Links Internet-Link

| ternet-Link | |
|---|--|
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |
| | |

last modified: 10/15/2016