## **SIEMENS**

## Data sheet

## 6GK5005-0BA00-1AB2

SCALANCE XB005 unmanaged Industrial Ethernet Switch for 10/100 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 5x 10/100 Mbit/s twisted pair ports with RJ45 sockets; Manual available as a download



Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	5; RJ45
Number of 100 Mbit/s SC ports	
• for multimode	0
Number of 1000 Mbit/s LC ports	
• for multimode	0
• for single mode (LD)	0
Interfaces / others	
Number of electrical connections	
<ul> <li>for power supply</li> </ul>	1
Type of electrical connection	
<ul> <li>for power supply</li> </ul>	3-pole terminal block
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	AC/DC

Supply voltage	
• external	24 V
• external / minimum	19.2 V
<ul> <li>external / maximum</li> </ul>	28.8 V
• at AC	24 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.07 A
Power loss [W]	
• at DC / at 24 V	1.68 W
Permitted ambient conditions	
Ambient temperature	
<ul> <li>during operation</li> </ul>	-10 +60 °C
<ul> <li>during storage</li> </ul>	-40 +80 °C
<ul> <li>during transport</li> </ul>	-40 +80 °C
Relative humidity	
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
Protection class IP	IP20
Design, dimensions and weight	
Design	Box
Width	45 mm
Height	100 mm
Depth	87 mm
Net weight	0.165 kg
Mounting type	
<ul> <li>35 mm DIN rail mounting</li> </ul>	Yes
<ul> <li>wall mounting</li> </ul>	Yes
• S7-1500 rail mounting	No
Product functions / management, configuration	
Product function	
multiport mirroring	No
• CoS	Yes
• switch-managed	No
Product functions / Redundancy	
Product function	No.
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
Standards, specifications, approvals	

Standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2,
	GP. IIC, T4
<ul> <li>for hazardous zone</li> </ul>	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc,
	KEMA 07ATEX0145 X
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1
<ul> <li>for emitted interference</li> </ul>	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2

Yes
IS
EN 61000-6-2, EN 61000-6-4
Yes
Yes
ormity
241 у
http://www.siemens.com/snst
http://www.siemens.com/snst http://www.siemens.com/simatic-net
http://www.siemens.com/simatic-net
http://www.siemens.com/simatic-net https://mall.industry.siemens.com
http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

02/13/2018