

Product type designation

SCALANCE XF206-1

SCALANCE XF206-1, FLAT, MANAGED IE SWITCH, 6 X 10/100MBIT/S RJ45 PORTS, 1 X 100MBIT/S FO PORT, FAULT SIGNAL CONTACT WITH SET- BUTTON, REDUNDANT POWER SUPPLY, PROFINET-IO DEVICE, NETWORKMANAGEMENT, RED.- MANAGER INTEGRATED, INCL. MANUAL ON CD, C-PLUG OPTIONAL



Transmission rate

Transfer rate	10 Mbit/s, 100 Mbit/s
---------------	-----------------------

Interfaces / for communication / integrated

Number of electrical connections	6
<ul style="list-style-type: none"> for network components or terminal equipment 	6
Number of 100 Mbit/s ST(BFOC) ports	1
<ul style="list-style-type: none"> for multimode 	1
Number of 100 Mbit/s SC ports	0
<ul style="list-style-type: none"> for multimode 	0
Number of 1000 Mbit/s LC ports	0
<ul style="list-style-type: none"> for multimode for single mode (LD) 	0

Interfaces / others

Number of electrical connections	1
<ul style="list-style-type: none"> for signaling contact 	1
<ul style="list-style-type: none"> for power supply 	1
<ul style="list-style-type: none"> for redundant voltage supply 	1

Type of electrical connection	2-pole terminal block 4-pole terminal block
design of the removable storage	Yes

Signal-Inputs/outputs

Operating voltage / of the signaling contacts	24 V
Operating current / of the signaling contacts	0.1 A

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	24 V 18 ... 32 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	1.1 A / 33 V
Consumed current / maximum	0.17 A
Power loss [W]	4.08 W

Permitted ambient conditions

Ambient temperature	-40 ... +60 °C -40 ... +70 °C -40 ... +70 °C If the IE switch XF 200 is installed horizontally a maximum ambient temperature of +40 °C is permitted
Relative humidity	95 %
Protection class IP	IP20

Design, dimensions and weight

Design	Flat
Width	75 mm
Height	125 mm
Depth	73 mm
Net weight	0.25 kg
Mounting type	Yes No No

- S7-1500 rail mounting

No

Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of $\leq 0.3\text{ s}$

100

Cascading in cases of star topology

any (depending only on signal propagation time)

Product functions / management, configuration

Product function

- CLI
- web-based management
- MIB support
- TRAPs via email
- Configuration with STEP 7
- Port mirroring
- multiport mirroring
- with IRT / PROFINET IO switch
- PROFINET IO diagnosis
- switch-managed

Yes
Yes
Yes
Yes
Yes
Yes
No
No
Yes
Yes

Protocol / is supported

- Telnet
- HTTP
- HTTPS
- TFTP
- FTP
- BOOTP
- DCP
- LLDP

Yes
Yes
Yes
Yes
Yes
No
Yes
Yes

Identification & maintenance function

- I&M0 - device-specific information
- I&M1 – higher-level designation/location designation

Yes
Yes

Protocol / is supported

- SNMP v1
- SNMP v2
- SNMP v3

Yes
Yes
Yes

Product functions / Diagnosis

Product function

- Port diagnostics
- Statistics Packet Size
- Statistics packet type
- Error statistics

Yes
Yes
Yes
Yes

Product functions / DHCP

Product function	
<ul style="list-style-type: none"> • DHCP client 	Yes

Product functions / Redundancy

Product function	
<ul style="list-style-type: none"> • Ring redundancy 	Yes
<ul style="list-style-type: none"> • High Speed Redundancy Protocol (HRP) 	Yes
<ul style="list-style-type: none"> • high speed redundancy protocol (HRP) with redundancy manager 	Yes
<ul style="list-style-type: none"> • high speed redundancy protocol (HRP) with standby redundancy 	No
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
Product function	
<ul style="list-style-type: none"> • media redundancy protocol (MRP) with redundancy manager 	Yes
<ul style="list-style-type: none"> • Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
<ul style="list-style-type: none"> • Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No
<ul style="list-style-type: none"> • Passive listening 	Yes

Product functions / Security

Protocol / is supported	
<ul style="list-style-type: none"> • SSH 	Yes

Product functions / Time

Product function	
<ul style="list-style-type: none"> • SICLOCK support 	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • NTP 	No
<ul style="list-style-type: none"> • SNTP 	Yes

Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> • for FM 	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
<ul style="list-style-type: none"> • for hazardous zone 	EN 60079-0: 2006, EN60079-15: 2005, II 3 (2) G Ex nA [op is] IIC T4, KEMA 07 ATEX 0145 X
<ul style="list-style-type: none"> • for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
<ul style="list-style-type: none"> • for hazardous zone / from CSA and UL 	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4
<ul style="list-style-type: none"> • for emitted interference 	EN 61000-6-4:2001 (Class A)
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2:2001
Certificate of suitability / CE marking	Yes

Certificate of suitability	EN 61000-6-2:2001, EN 61000-6-4:2001
<ul style="list-style-type: none"> • C-Tick • Railway application in accordance with EN 50155 • Railway application in accordance with EN 50124-1 • KC approval 	<p>Yes</p> <p>No</p> <p>No</p> <p>Yes</p>
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • Bureau Veritas (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) • Royal Institution of Naval Architects (RINA) 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>No</p>
MTBF / at 40 °C	43.52 y

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support 	<p>http://www.siemens.com/snst</p> <p>http://www.siemens.com/simatic-net</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

12.05.2016