



Figure similar

Ordering data

6SL3210-1PB17-4UL0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data

Input

Number of phases	1 / 3 AC
Line voltage	200 ... 240 V \pm 10 %
Line frequency	47 ... 63 Hz
Rated current (LO)	18.10 / 10.50 A
Rated current (HO)	15.80 A

Output

Number of phases	3 AC
Rated voltage	230 V
Rated power (LO)	1.50 kW / 2.00 hp
Rated power (HO)	1.10 kW / 1.50 hp
Rated current (LO)	7.40 A
Rated current (HO)	6.00 A
Max. output current	12.00 A
Pulse frequency	4 kHz
Output frequency for vector control	0 ... 200 Hz
Output frequency for V/f control	0 ... 550 Hz

General tech. specifications

Power factor λ	0.85
Offset factor $\cos \phi$	0.95
Efficiency η	0.96
Sound pressure level (1m)	62 dB
Power loss	0.07 kW

Ambient conditions

Cooling	Internal air cooling
Cooling air requirement	0.009 m ³ /s
Installation altitude	1000 m
Ambient temperature	
Operation LO	-5 ... 40 °C (23 ... 104 °F)
Operation HO	-5 ... 50 °C (23 ... 122 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)

Relative humidity

Max. operation	95 % RH, condensation not permitted
----------------	-------------------------------------

Overload capability

Low Overload (LO)

1.1 × output current rating (i.e., 110 % overload) for 57 s with a cycle time of 300 s
1.5 × output current rating (i.e., 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 × output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s
2 × output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s



Figure similar

Ordering data

6SL3210-1PB17-4UL0

Mechanical data		Connections	
Degree of protection	IP20	Line side	
Size	FSB	Version	Plug-in screw-type terminals
Net weight	2.90 kg	Conductor cross-section	1.50 ... 6.00 mm ²
Width	100.0 mm	Motor end	
Height	292.0 mm	Version	Plug-in screw-type terminals
Depth	165.0 mm	Conductor cross-section	1.50 ... 6.00 mm ²
		Max. motor cable length	
		Shielded	50 m
		Unshielded	100 m
Standards			
Compliance with standards		UL, cUL, CE, C-Tick (RCM), SEMI F47	
CE marking		According to low-voltage directive 2006/95/EC	