



Figure similar

Ordering data

6SL3243-0BB30-1CA3

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Electrical data

Operating voltage via

The Power Module	DC 24 V
External power supply	DC 20 ... 29 V
Max. power consumption	0.50 A
Power loss	5.50 W

Inputs/ outputs

Standard digital inputs

Number	6
Switching level: 0→1	11 V
Switching level: 1→0	5 V

Fail-safe digital inputs

Number	0 (No fail-safe inputs available)
--------	-----------------------------------

Digital outputs

Number as relay changeover contact	2
Output (inductive load)	DC 250 V, 2 A
Output (resistive load)	DC 30 V, 1 A
Number as relay NO contact	1
Output (resistive load)	DC 30 V, 1 A

Analog/ digital inputs

Number	2 (Differential input)
--------	------------------------

Analog outputs

Number	2 (Non-isolated output)
--------	-------------------------

Connections

Signal cable

Conductor cross-section	0.15 ... 1.50 mm ² (28 ... 16 AWG)
-------------------------	---

Ambient conditions

Ambient temperature

Operation	-10 ... 60 °C (14 ... 140 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)

Relative humidity

Max. operation	95 %
----------------	------

Communication

Communication	CANopen
---------------	---------

Closed-loop control techniques

V/f linear / square-law / parameterizable	Yes
V/f with flux current control (FCC)	Yes
V/f ECO linear / square-law	Yes
Sensorless vector control	Yes
Vector control, with sensor	No
Encoderless torque control	Yes
Torque control, with encoder	No

Standards

Compliance with standards	UL, cUL, CE, C-Tick (RCM)
CE marking	
Low-voltage directive 2006/95/EC	

Mechanical data

Degree of protection	IP20
Net weight	0.61 kg
Width	73.0 mm
Height	199.0 mm
Depth	65.5 mm