



Figure similar

### Ordering data

6SL3244-0BB00-1BA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Electrical data

#### Operating voltage via

The Power Module	DC 24 V
External power supply	DC 20 ... 29 V
Max. power consumption	0.50 A
Power loss	5.50 W

### Inputs/ outputs

#### Standard digital inputs

Number	4
Switching level: 0→1	11 V
Switching level: 1→0	5 V

#### Fail-safe digital inputs

Number	0
--------	---

#### Digital outputs

Number as relay changeover contact	1
------------------------------------	---

#### Analog/ digital inputs

Number	1 (Differential input)
--------	------------------------

#### Analog outputs

Number	1 (Non-isolated output)
--------	-------------------------

### Connections

#### Signal cable

Conductor cross-section	0.05 ... 1.50 mm <sup>2</sup> (30 ... 16 AWG)
-------------------------	---

### Ambient conditions

#### Ambient temperature

Operation	-10 ... 55 °C (14 ... 131 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)

#### Relative humidity

Max. operation	95 %
----------------	------

### Communication

Communication	RS485
---------------	-------

### Closed-loop control techniques

V/f linear / square-law / parameterizable	Yes
V/f with flux current control (FCC)	Yes
V/f ECO linear / square-law	Yes
Sensorless vector control	Yes
Vector control, with sensor	No
Encoderless torque control	Yes
Torque control, with encoder	No

### Standards

Compliance with standards	UL, cUL, CE, C-Tick (RCM)
CE marking	
Low-voltage directive 2006/95/EC	

### Mechanical data

Degree of protection	IP20
Net weight	0.49 kg
Width	73.0 mm
Height	199.0 mm
Depth	46.0 mm