

Round plug connector IE Fast Connect Plug PRO M12 (D-coded)

Use

The customizable connectors are used to connect the Ethernet and PROFINET cable to the device or as coupling in rough environments.

How to use

The customizable M12x1 connectors permit an easy on-site assembly. The connectors for Ethernet / PROFINET are 4-pole types, D-coded. The shield is contacted through the connector housing. The connectors have a shielded metal housing.

Bus connection

- M12 (d-coded)
- Fast Connect
- Axial (180°)
- Transfer speed: 10/100 MBit/s

Electrical parameters

- Transfer speed: 10 / 100 Mbps
- Number of electrical connections: For IE FC TP Lines - 4
For Network components - 1
For Devices - 1
- Electrical connections: For IE FC TP integrated insulation displacement contacts for 4-wire TP FC installation lines for Network components or devices - M12 connector (D-coded)

Ambient conditions

- Operating temperature: -40°C to +85°C
- Protection type: IP65/67 when connected and screwed (DIN VDE 0470)

Constructive design

- Weight: 40 g
- Housing: Metal
- Dimensions (WxHxD): 19 x 19 x 73 mm
- Contact surface: Brass alloy (CuSnZn)
- Connection cross-section: Max. 0.75 mm²

CE mark

Plugs are passive components and are not subject to the CE mark system pursuant to EU Directives.

Ordering details

Art. No.

Circular connector IE Fast Connect Plug PRO M12 (d-coded)


114030002



Circular connector IE Fast Connect Plug PRO M12 (D-coded)




Sample application (side view)



Sample application (view from above)

M12 Stecker



Signal	Designation	Wire color	Assignment	
TD+	Transmission Data +	yellow	RJ45 1	M12 1
TD-	Transmission Data -	orange	2	3
RD+	Receive Data +	white	3	2
RD-	Receive Data -	blue	6	4

Pin assignment