

### Indu-Sol GmbH - Specialist in Industrial Networks

# Connector RJ45 Fast Connect Plug 180°/90°

#### Function

The **RJ45 Fast Connect Plug 180°/90° Plug** allows for the connection of different PROFINET components with each other or to end devices, e.g. a PROFINET station to a PROFINET cable. A single connection can be up to 100 m in length. The contact elements have colour markings to simplify connection and avoid mistakes. After connection, a visual check can be done. The plug is used for data transfer rates of up to 100 Mbps.

# Application

The plug is available as a straight or elbow version. Thanks to the rugged metal housing and the RJ45 Fast Connector the plug is suitable for industrial use.

### Technical data RJ45 Fast Connect Plug 180°

• Number of electrical connections:

	for IE FC TP lines -4
	for network components/devices - 1
• Wiring check:	Visual
• Contact Elements:	Colour-coded, help to avoid connection
	errors
<ul> <li>Fast Connect:</li> </ul>	Yes
<ul> <li>For IE FC TP lines:</li> </ul>	Integr. insulation displacement contacts
<ul> <li>For network/devices:</li> </ul>	RJ45-Connector
<ul> <li>Transmission with Cat5e:</li> </ul>	100 MBit/s
<ul> <li>Transmission rate:</li> </ul>	Max. 100 Mbit/s
<ul> <li>Storage temperature:</li> </ul>	-40 to +80 °C
<ul> <li>Ambient temperature:</li> </ul>	-20 to +70 °C
<ul> <li>Permissible humidity</li> </ul>	Max. 95 %
<ul> <li>Housing:</li> </ul>	Industrial-suited metal housing
• Weight:	Approx. 30 g
• Dimensions (H x W x D):	56,5 x 16,4 x 14,0 mm

• Industrial protection: IP20

# Technical data RJ45 Fast Connect Plug 90°

• Number of electrical connections:

	for IE FC TP lines -4
	for network components/devices - 1
<ul> <li>Wiring check:</li> </ul>	Visual
• Contact Elements:	Colour-coded, help to avoid connection errors
<ul> <li>Fast Connect:</li> </ul>	Yes
<ul> <li>For IE FC TP lines:</li> </ul>	Integr. insulation displacement contacts
<ul> <li>For network/devices:</li> </ul>	RJ45-Connector
<ul> <li>Transmission with Cat5e:</li> </ul>	100 MBit/s
<ul> <li>Transmission rate:</li> </ul>	Max. 100 Mbit/s
<ul> <li>Storage temperature:</li> </ul>	-40 to +80 °C
<ul> <li>Ambient temperature:</li> </ul>	-20 to +70 °C
<ul> <li>Permissible humidity:</li> </ul>	Max. 95 %
<ul> <li>Housing:</li> </ul>	Industrial-suited metal housing
• Weight:	Approx. 35 g
• Dimensions (H x W x D):	43,5 x 40,5 x 16,2 mm
<ul> <li>Industrial protection:</li> </ul>	IP20

Ordering detailsArt. No.Connector RJ45 Fast Connect Plug 180°114030006Connector RJ45 Fast Connect Plug 90°114030004



#### Connector RJ45 Fast Connect Plug 180°



Connector RJ45 Fast Connect Plug 90°