SIEMENS

Data sheet

6ES7193-6BP60-0DA0

SIMATIC ET 200SP, 2-fold BaseUnit, BU type A0, 2BU15-P16+A0+2DB, Packing unit (PU) 1, push-in terminals, without auxiliary terminals, new potential group, WxH: 30 x 117 mm



General information	
Product type designation	2x BU type A0, light-dark version, without AUX terminals
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Mains filter	
• integrated	Yes
Current carrying capacity	
For P1 and P2 bus, max.	10 A
For process terminals, max.	2 A
Hardware configuration	
Formation of potential groups	
 New potential group 	Yes
 Potential group continued from the left 	No
Isolation	
Isolation tested with	707 V DC (type test)

Ambient conditions	
Ambient temperature during operation	
 horizontal installation, min. 	0 °C; On request: Ambient temperatures lower than 0 °C (without condensation)
 horizontal installation, max. 	60 °C
 vertical installation, min. 	0 °C; On request: Ambient temperatures lower than 0 °C (without condensation)
 vertical installation, max. 	50 °C
Altitude during operation relating to sea level	
 Installation altitude above sea level, max. 	2 000 m; On request: Installation altitudes greater than 2 000 m
Accessories	
Color coding labels	
 for process terminals 	CC00 to CC09
 for AUX terminals 	does not exist
• for add-on terminals	does not exist
Connection method	
Terminals	
 Terminal type 	Push-in terminal
 Conductor cross-section, min. 	0.14 mm²; AWG 26
 Conductor cross-section, max. 	2.5 mm²; AWG 14
 Number of process terminals to I/O module 	16; Pro slot
 Number of terminals to AUX bus 	0
 Number of add-on terminals 	0
 Number of terminals with connection to P1 and P2 bus 	2; Pro slot
Dimensions	
Width	30 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	80 g
last modified:	11/27/2018