



*** Spare part *** LOGO! AM2 RTD expansion module, PS: 12/24 V DC, 2AI-50...+200 °C Pt100/1000

Installation type/mounting	
Mounting	on 35 mm DIN rail, 2 spacing units wide
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> 12 V DC 24 V DC 	Yes; 10.8 V DC to 28.8 V DC Yes; 10.8 V DC to 28.8 V DC
Input current	
Current consumption, typ.	40 mA
Analog inputs	
Number of analog inputs	2; 2 or 3 wire connection
Input ranges	
<ul style="list-style-type: none"> Voltage Current Resistance thermometer 	No No Yes; For PT100/PT1000 sensors
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> 0 to +10 V 	No
Input ranges (rated values), currents	
<ul style="list-style-type: none"> 0 to 20 mA 	No
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> Pt 100 	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> Limit class B, for use in residential areas 	Yes; Radio interference suppression according to EN55011, Limit Value Class B
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes; C22.2 Number 142
UL approval	Yes; UL 508
FM approval	Yes; FM-Standards No. 3611, 3600, 3810 Class I, Division 2, Group A, B, C, D
developed in accordance with IEC 61131	Yes; EN 61131-2 (IEC 1131-2)
Marine approval	Yes; ABS, BV, DNV, GL, LRS, Class NK
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. 	0 °C 55 °C
Dimensions	
Width	36 mm

Height
Depth

90 mm
53 mm

last modified:

3/12/2021 