



SIMATIC S7-1500, analog output module AQ 4xU/I HF, 16-bit resolution accuracy 0.1%, 4 channels in groups of 1, common mode voltage: 30 V AC/60 V DC, diagnostics; substitute value, isochronous mode; the module supports the safety-oriented shutdown of load groups up to SIL2 according to EN IEC 62061:2021 and Category 3 / PL d according to EN ISO 13849-1:2015. delivery including infeed element, shielding bracket and shield terminal: front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	AQ 4xU/I HF
HW functional status	From FS01
Firmware version	V1.1.0
<ul style="list-style-type: none"> FW update possible 	Yes
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Isochronous mode 	Yes
<ul style="list-style-type: none"> Prioritized startup 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	V14 / -
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	V5.5 SP3 / -
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	V1.0 / V5.1
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> Oversampling 	No
<ul style="list-style-type: none"> MSO 	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	160 mA
Power	
Power available from the backplane bus	0.95 W
Power loss	
Power loss, typ.	5 W
Analog outputs	
Number of analog outputs	4
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	24 mA
Current output, no-load voltage, max.	22 V
Cycle time (all channels), min.	125 µs; independent of number of activated channels
Output ranges, voltage	
<ul style="list-style-type: none"> 0 to 10 V 	Yes

<ul style="list-style-type: none"> • 1 V to 5 V 	Yes
<ul style="list-style-type: none"> • -5 V to +5 V 	No
<ul style="list-style-type: none"> • -10 V to +10 V 	Yes
Output ranges, current	
<ul style="list-style-type: none"> • 0 to 20 mA 	Yes
<ul style="list-style-type: none"> • -20 mA to +20 mA 	Yes
<ul style="list-style-type: none"> • 4 mA to 20 mA 	Yes
Connection of actuators	
<ul style="list-style-type: none"> • for voltage output two-wire connection 	Yes
<ul style="list-style-type: none"> • for voltage output four-wire connection 	Yes
<ul style="list-style-type: none"> • for current output two-wire connection 	Yes
Load impedance (in rated range of output)	
<ul style="list-style-type: none"> • with voltage outputs, min. 	1 k Ω ; 0.5 k Ω m at 1 to 5 V
<ul style="list-style-type: none"> • with voltage outputs, capacitive load, max. 	1 μ F
<ul style="list-style-type: none"> • with current outputs, max. 	750 Ω
<ul style="list-style-type: none"> • with current outputs, inductive load, max. 	10 mH
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	800 m; for current, 200 m for voltage
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	16 bit
<ul style="list-style-type: none"> • Conversion time (per channel) 	125 μ s; independent of number of activated channels
Settling time	
<ul style="list-style-type: none"> • for resistive load 	0.2 ms; see additional description in the manual
<ul style="list-style-type: none"> • for capacitive load 	1.8 ms; see additional description in the manual
<ul style="list-style-type: none"> • for inductive load 	2 ms; see additional description in the manual
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.015 %
Temperature error (relative to output range), (+/-)	0.002 %/K
Crosstalk between the outputs, max.	-100 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.005 %
note regarding accuracy	at temperatures below 0 °C, the figures for operating error and temperature error are doubled
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to output range, (+/-) 	\pm 10 V; 0 V to 10 V: \pm 0.12%; 1 V to 5 V: \pm 0.1%
<ul style="list-style-type: none"> • Current, relative to output range, (+/-) 	\pm 20 mA; 0 mA to 20 mA: \pm 0.2%; 4 mA to 20 mA: \pm 0.12%
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to output range, (+/-) 	0.06 %
<ul style="list-style-type: none"> • Current, relative to output range, (+/-) 	0.1 %
Isochronous mode	
Execution and activation time (TCO), min.	100 μ s
Bus cycle time (TDP), min.	250 μ s
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage 	Yes
<ul style="list-style-type: none"> • Wire-break 	Yes; Only for output type "current"
<ul style="list-style-type: none"> • Short-circuit 	Yes; Only for output type "voltage"
<ul style="list-style-type: none"> • Overflow/underflow 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • RUN LED 	Yes; green LED
<ul style="list-style-type: none"> • ERROR LED 	Yes; red LED
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) 	Yes; green LED
<ul style="list-style-type: none"> • Channel status display 	Yes; green LED
<ul style="list-style-type: none"> • for channel diagnostics 	Yes; red LED
<ul style="list-style-type: none"> • for module diagnostics 	Yes; red LED
Potential separation	

Potential separation channels	
<ul style="list-style-type: none"> • between the channels • between the channels, in groups of • between the channels and backplane bus • Between the channels and load voltage L+ 	Yes 1 Yes Yes
Permissible potential difference	
between different circuits	60 V DC/30 V AC; insulation rated for 120 V AC basic insulation: between the channels and the supply voltage L+; between the channels and the backplane bus; between the channels
Isolation	
Isolation tested with	2 000 V DC between the channels and the supply voltage L+; 2 000 V DC between the channels and the backplane bus; 2 000 V DC between the channels; 707 V DC (type test) between the supply voltage L+ and the backplane bus
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	Yes; From FS03
Highest safety class achievable for safety-related tripping of standard modules	
<ul style="list-style-type: none"> • Performance level according to ISO 13849-1 • Category according to ISO 13849-1 • SIL acc. to IEC 62061 • remark on safety-oriented shutdown 	PL d Cat. 3 SIL 2 https://support.industry.siemens.com/cs/de/de/view/39198632
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. 	-25 °C; From FS02 60 °C -25 °C; From FS02 40 °C
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	300 g
last modified:	4/27/2022 