



FRONT CONN. MOD.(DIGITAL 1X50 P) S7-1500

Front connector module with 1x50 pole IDC connector for digital 32 I/O modules of the S7-1500 Potential supply over Push-in terminal

target system
suitability for use
product type designation
product designation

SIMATIC S7-1500
Digital I/O modules
Fully modular connection
Front connector module

Operating data / header

operating voltage	
• at DC / rated value	24 V
• rated value	24 V
• at DC / maximum	60 V
continuous current / at DC / per plug-in contact / maximum	1 A
total current / maximum	2 A; for mounting position horizontal
operating temperature	0 ... 60 °C
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
number of poles	40; of the front connector
manufacturer's article number / of device connector / usable	replacement for S7-1500 40 pole
number of the plug contacts / of the electrical connection	1
type of electrical connection / for connecting cable	Plug-in connection
number of poles / at the 1st interface	50; the IDC connector for the connection cable
position / of the terminal	at the top
type of electrical connection / for power supply	Push-In terminal
number of terminals	4; 4 x 1 x L+
width of screwdriver blade	3.5 mm
product component / required / end cover plate	No
number of cables / per connection	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
stripped length	8 mm
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	
• for flexible conductor / with core end processing	0.25 ... 1.5 mm ² ; End sleeve according to DIN 46228/1 or DIN 46228/4 with plastic collar max. 0.75 mm ²
• stranded	0.5 ... 1.5 mm ²
• finely stranded / without core end processing	0.5 ... 1.5 mm ²
• finely stranded / with core end processing	0.25 ... 1.5 mm ²
type of wire end sleeve	
• without plastic sleeve / according to DIN 46228-1	Length 8mm to 9mm
• with plastic sleeve / according to DIN 46228-4	Length 8mm to 9mm
outer diameter / of the wire insulation	3.1 mm; to the connection of the supply terminal
wire length / maximum	30 m; between front connector module and terminal module

General data / header

mounting type
degree of pollution
overvoltage category
design tested acc. to type of protection / EEx e
certificate of suitability / cULus approval
reference code / according to IEC 81346-2
material / of the insulating body
color / of the enclosure
product feature / transparent
net weight

direct mounting
2
2
No
Yes
XG
other
black
No
0.099 kg

last modified:

7/12/2022 