

product type designation



CM 1243-5

communications module CM 1243-5 for connection of SIMATIC S7-1200 to PROFIBUS as DP Master module; PG/OP communication; S7 communication.

transfer rate

transfer rate

- at the 1st interface / according to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

interfaces

- | | |
|------------------------------------------------------------------------------------------------|----------------------------|
| number of interfaces / according to Industrial Ethernet | 0 |
| number of electrical connections | |
| <ul style="list-style-type: none"> at the 1st interface / according to PROFIBUS | 1 |
| <ul style="list-style-type: none"> for power supply | 1 |
| type of electrical connection | |
| <ul style="list-style-type: none"> at the 1st interface / according to PROFIBUS | 9-pin Sub-D socket (RS485) |
| <ul style="list-style-type: none"> for power supply | 3-pole terminal block |

supply voltage, current consumption, power loss

- | | |
|------------------------------------------------------------------------------------------------------------|-------|
| type of voltage / of the supply voltage | DC |
| supply voltage / external | 24 V |
| supply voltage / external / at DC / rated value | 24 V |
| relative positive tolerance / at DC / at 24 V | 20 % |
| relative negative tolerance / at DC / at 24 V | 20 % |
| consumed current | |
| <ul style="list-style-type: none"> from external supply voltage / at DC / at 24 V / typical | 0.1 A |
| power loss [W] | 2.4 W |

ambient conditions

- | | |
|----------------------------------------------------------------------------------------------------------------|----------------|
| ambient temperature | |
| <ul style="list-style-type: none"> for vertical installation / during operation | 0 ... 45 °C |
| <ul style="list-style-type: none"> for horizontally arranged busbars / during operation | 0 ... 55 °C |
| <ul style="list-style-type: none"> during storage | -40 ... +70 °C |
| <ul style="list-style-type: none"> during transport | -40 ... +70 °C |
| relative humidity | |
| <ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |

design, dimensions and weights

- | | |
|-----------------------------------------------------------------------------------|-------------------------------------|
| module format | Compact module S7-1200 single width |
| width | 30 mm |
| height | 100 mm |
| depth | 75 mm |
| net weight | 0.134 kg |
| fastening method | |
| <ul style="list-style-type: none"> 35 mm top hat DIN rail mounting | Yes |
| <ul style="list-style-type: none"> S7-300 rail mounting | No |

<ul style="list-style-type: none"> • wall mounting 	Yes
product features, product functions, product components / general	
number of units	
<ul style="list-style-type: none"> • per CPU / maximum 	3
performance data / PROFIBUS DP	
service / as DP master	
<ul style="list-style-type: none"> • DPV1 	Yes
number of DP slaves	
<ul style="list-style-type: none"> • on DP master / operable 	32
data volume	
<ul style="list-style-type: none"> • of the address range of the inputs / as DP master / total 	512 byte
<ul style="list-style-type: none"> • of the address range of the outputs / as DP master / total 	512 byte
<ul style="list-style-type: none"> • of the address range of the inputs / per DP slave 	244 byte
<ul style="list-style-type: none"> • of the address range of the outputs / per DP slave 	244 byte
<ul style="list-style-type: none"> • of the address range of the diagnostic data / per DP slave 	240 byte
service / as DP slave	
<ul style="list-style-type: none"> • DPV0 	No
<ul style="list-style-type: none"> • DPV1 	No
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> • maximum 	8; max. 4 connections to other S7 stations
<ul style="list-style-type: none"> • with PG connections / maximum 	1
<ul style="list-style-type: none"> • with PG/OP connections / maximum 	3
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> • without DP / maximum 	8
<ul style="list-style-type: none"> • with DP / maximum 	8
performance data / telecontrol	
protocol / is supported	
<ul style="list-style-type: none"> • TCP/IP 	No
product functions / management, configuration, engineering	
configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 Basic/Professional
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4)

last modified:

7/7/2022 

