## **SIEMENS**

## Data sheet

## 6GK5204-0JA00-2BA6



SCALANCE X204IRT PRO, managed IE IRT switch with degree of protection IP65/67, 4x 10/100 Mbit/s Push-pull RJ45 ports, error signaling contact with set button; redundant power supply; PROFINET IO device, network management, Redundancy Manager integrated, incl. electron. manual on CD-ROM, C-plug optional

Product type designation	SCALANCE X204IRT PRO
Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / Integrated	
Number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	4
Interfaces / other	
Number of electrical connections	
<ul> <li>for signaling contact</li> </ul>	1
• for power supply	1
Type of electrical connection	
<ul> <li>for signaling contact</li> </ul>	5-pin M12 socket
• for power supply	5-pin push-pull plug PRO socket
design of the removable storage	
• C-PLUG	Yes
Signal inputs/outputs	
Operating voltage / of the signaling contacts	

• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V
• external / minimum	18 V
• external / maximum	32 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.2 A
Power loss [W]	
• at DC / at 24 V	4.8 W
Ambient conditions	
Ambient temperature	
<ul> <li>during operation</li> </ul>	-25 +70 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
Relative humidity	-
<ul> <li>at 25 °C / without condensation / during</li> </ul>	95 %
operation / maximum	
Protection class IP	IP65
Design	compact
Width	90 mm
Height	125 mm
Depth	124 mm
Net weight	1 kg
Mounting type	-
• 35 mm DIN rail mounting	Yes
<ul> <li>wall mounting</li> </ul>	Yes
<ul> <li>S7-300 rail mounting</li> </ul>	Yes
• S7-1500 rail mounting	No
Product features, product functions, product components / general	
Cascading in the case of a redundant ring / at	100
reconfiguration time of ~0.3\~s</td <td></td>	
Cascading in cases of star topology	any (depending only on signal propagation time)
Product functions / management, configuration, engineering	
Product functions / management, configuration, en	

MIB support	Yes
• TRAPs via email	Yes
<ul> <li>Configuration with STEP 7</li> </ul>	Yes
Port mirroring	No
multiport mirroring	No
<ul> <li>with IRT / PROFINET IO switch</li> </ul>	Yes
PROFINET IO diagnosis	Yes
PROFINET conformity class	В
Product function / switch-managed	Yes
Protocol / is supported	
Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	No
• DCP	Yes
• LLDP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
Identification & maintenance function	
<ul> <li>I&amp;M0 - device-specific information</li> </ul>	Yes
<ul> <li>I&amp;M1 – higher-level designation/location</li> </ul>	Yes
designation	
Product functions / Diagnostics	
Product function	
<ul> <li>Port diagnostics</li> </ul>	Yes
Statistics Packet Size	Yes
<ul> <li>Statistics packet type</li> </ul>	Yes
• Error statistics	Yes
Product functions / DHCP	
Product function	Yes.
DHCP client	Yes
Product functions / redundancy	
Product function	
<ul> <li>Ring redundancy</li> </ul>	Yes
<ul> <li>High Speed Redundancy Protocol (HRP)</li> </ul>	Yes
<ul> <li>high speed redundancy protocol (HRP) with</li> </ul>	Yes
redundancy manager	

<ul> <li>high speed redundancy protocol (HRP) with standby redundancy</li> </ul>	Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
Product function	
<ul> <li>media redundancy protocol (MRP) with redundancy manager</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
Passive listening	Yes
Product functions / Security	
Protocol / is supported	
• SSH	Yes
Product functions / time	
Product function	
<ul> <li>SICLOCK support</li> </ul>	Yes
Protocol / is supported	
• NTP	No
• SNTP	Yes
Standards, specifications, approvals	
Standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA
<ul> <li>for hazardous zone</li> </ul>	07 ATEX 0145X
<ul> <li>for hazardous zone</li> <li>for safety / from CSA and UL</li> </ul>	
	07 ATEX 0145X
● for safety / from CSA and UL	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 /
<ul> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> </ul>	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4
<ul> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> </ul>	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4 EN 61000-6-4:2001 (Class A)
<ul> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul>	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4 EN 61000-6-4:2001 (Class A)
<ul> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul> Standards, specifications, approvals / CE	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4 EN 61000-6-4:2001 (Class A) EN 61000-6-4:2001
<ul> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul> Standards, specifications, approvals / CE Certificate of suitability / CE marking	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4 EN 61000-6-4:2001 (Class A) EN 61000-6-4:2001
<ul> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul> Standards, specifications, approvals / CE Certificate of suitability / CE marking Standards, specifications, approvals / other	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4 EN 61000-6-4:2001 (Class A) EN 61000-6-4:2001
<ul> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul> Standards, specifications, approvals / CE Certificate of suitability / CE marking Standards, specifications, approvals / other Certificate of suitability	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4 EN 61000-6-4:2001 (Class A) EN 61000-6-4:2001 Yes EN 61000-6-4:2001
<ul> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul> Standards, specifications, approvals / CE Certificate of suitability / CE marking Standards, specifications, approvals / other Certificate of suitability <ul> <li>C-Tick</li> <li>Railway application in accordance with EN</li> </ul>	07 ATEX 0145X UL 60950-1, CSA C22.2 No. 60950-1 ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4 EN 61000-6-4:2001 (Class A) EN 61000-6-4:2001 Yes EN 61000-6-4:2001 Yes

Standards, specifications, approvals / marine class	ification
Marine classification association	
<ul> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
• Bureau Veritas (BV)	Yes
• DNV GL	Yes
<ul> <li>Lloyds Register of Shipping (LRS)</li> </ul>	Yes
<ul> <li>Nippon Kaiji Kyokai (NK)</li> </ul>	Yes
<ul> <li>Polski Rejestr Statkow (PRS)</li> </ul>	Yes
<ul> <li>Royal Institution of Naval Architects (RINA)</li> </ul>	Yes
Standards, specifications, approvals / Product conf	formity
MTBF	98.55 у
accessories	
Product extension / optional / C-PLUG	Yes
Further information / Internet-Links	
Internet-Link	
to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
<ul> <li>to website: Industrial communication</li> </ul>	http://www.siemens.com/simatic-net
<ul> <li>to website: Industry Mall</li> </ul>	https://mall.industry.siemens.com
<ul> <li>to website: Information and Download Center</li> </ul>	http://www.siemens.com/industry/infocenter
<ul> <li>to website: Image database</li> </ul>	http://automation.siemens.com/bilddb
<ul> <li>to website: CAx Download Manager</li> </ul>	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
Security information	
Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third- party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	11/11/2019