

SIMATIC ET 200SP, DIGITAL INPUT MODULE, DI 16X 24VDC STANDARD, FITS TO BU-TYPE A0, COLOR CODE CC00, MODULE DIAGNOSIS



General information	
Product type designation	ET 200SP, DI 16x24VDC ST, VPE 1
Firmware version	V1.1
<ul style="list-style-type: none"> FW update possible 	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V13 SP1
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 / -
<ul style="list-style-type: none"> PCS 7 configurable/integrated as of version 	V8.1 SP1
<ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision 	GSD Revision 5
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	GSDML V2.3
Operating mode	
<ul style="list-style-type: none"> DI 	Yes
<ul style="list-style-type: none"> Counter 	No

- Oversampling
- MSI

No

No

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption, max.	90 mA
---------------------------	-------

Encoder supply

Short-circuit protection	No
--------------------------	----

24 V encoder supply

- 24 V No
- Short-circuit protection No

Power loss

Power loss, typ.	1.7 W
------------------	-------

Address area

Address space per module

- Address space per module, max. 2 byte; + 2 bytes for QI information

Hardware configuration

Automatic encoding

- Mechanical coding element Yes

Selection of BaseUnit for connection variants

- 1-wire connection BU type A0
- 2-wire connection BU type A0 + external terminals
- 3-wire connection BU type A0 + external terminals
- 4-wire connection BU type A0 + external terminals

Digital inputs

Number of digital inputs	16
m/p-reading	p-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 2	No
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Pulse extension	No

Input voltage

- Type of input voltage DC
- Rated value (DC) 24 V

• for signal "0"	-30 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms (in each case + delay of 30 to 500 µs, depending on line length)
— at "0" to "1", min.	0.05 ms
— at "0" to "1", max.	20 ms
— at "1" to "0", min.	0.05 ms
— at "1" to "0", max.	20 ms
for interrupt inputs	
— parameterizable	No
for counter/technological functions	
— parameterizable	No
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Diagnostics	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes
— parameterizable	Yes
• Monitoring of encoder power supply	No
• Wire-break	Yes; Module-wise
• Short-circuit	No
• Group error	Yes
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED

- Channel status display
- for channel diagnostics
- for module diagnostics

Yes; Green LED
 No
 Yes; green/red DIAG LED

Potential separation

Potential separation channels

- between the channels
- between the channels and backplane bus
- between the channels and the power supply of the electronics

No
 Yes
 No

Permissible potential difference

between different circuits

75 V DC/60 V AC (base isolation)

Isolation

Isolation tested with

707 V DC (type test)

Dimensions

Width

15 mm

Height

73 mm

Depth

58 mm

Weights

Weight, approx.

28 g

last modified:

14.05.2016