

Siemens
EcoTech



SIMATIC S7-1200 G2: SM 1223 digital I/O, 8 DI/8 DO inputs: 8x DI 24 V DC sink/source outputs: 8x DO, 24 V DC 0.5 A, sourcing transistor

Figure similar

General information	
Product type designation	SM 1223, DI 8x 24 V DC, DQ 8x 24 V DC 0.5A
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	110 mA
Digital inputs	
<ul style="list-style-type: none"> from load voltage L+ (without load), max. 	4.1 mA; per channel
Digital outputs	
<ul style="list-style-type: none"> from load voltage L+, max. 	45 mA
Power loss	
Power loss, typ.	4 W
Digital inputs	
Number of digital inputs	8
<ul style="list-style-type: none"> in groups of 	4
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8
horizontal installation	
— up to 40 °C, max.	8
— up to 50 °C, max.	8
vertical installation	
— up to 40 °C, max.	8
Input voltage	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> for signal "0" 	5 V DC or 0.5 mA
<ul style="list-style-type: none"> for signal "1" 	15 V DC at 2.5 mA
Input current	
<ul style="list-style-type: none"> for signal "0", max. (permissible quiescent current) 	1 mA
<ul style="list-style-type: none"> for signal "1", min. 	2.5 mA
<ul style="list-style-type: none"> for signal "1", typ. 	4.1 mA
Input delay (for rated value of input voltage)	

for standard inputs	
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
for interrupt inputs	
— Parameterizable	No
Cable length	
• shielded, max.	500 m
• unshielded, max.	300 m
Digital outputs	
Number of digital outputs	8
• in groups of	8
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	typ. (L+) -40 V, 1 W dissipation
Switching capacity of the outputs	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
Output voltage	
• Rated value (DC)	24 V
• for signal "0", max.	0.1 V; with 10 kOhm load
• for signal "1", min.	20 V DC
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, max.	0.5 A
• for signal "0" residual current, max.	10 µA
Output delay with resistive load	
• "0" to "1", max.	50 µs
• "1" to "0", max.	200 µs
Total current of the outputs (per group)	
horizontal installation	
— up to 50 °C, max.	2 A; Current per mass
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
Diagnostics indication LED	
• DIAG LED	Yes
• for status of the inputs	Yes
• for status of the outputs	Yes
Potential separation	
Potential separation digital inputs	
• between the channels, in groups of	4
• between the channels and backplane bus	Yes; 707 V DC (type test)
Potential separation digital outputs	
• between the channels, in groups of	8
• between the channels and backplane bus	Yes; 707 V DC (type test)
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
CE mark	Yes
CSA approval	No
UL approval	Yes

cULus	Yes	
FM approval	No	
RCM (formerly C-TICK)	Yes	
KC approval	Yes	
Marine approval	No	
Ecological footprint		
• environmental product declaration	Yes; type 2 acc. to ISO 14021	
Global warming potential		
— global warming potential, (total) [CO2 eq]	40.3 kg	
— global warming potential, (during production) [CO2 eq]	7.79 kg	
— global warming potential, (during operation) [CO2 eq]	32.5 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-0.089 kg	
Ambient conditions		
Free fall		
• Fall height, max.	0.3 m; five times, in product package	
Ambient temperature during operation		
• horizontal installation, min.	-20 °C	
• horizontal installation, max.	60 °C; at max. voltages and max. specification	
• vertical installation, min.	-20 °C	
• vertical installation, max.	50 °C; at max. voltages and max. specification	
• permissible temperature change	5°C to 55°C, 3°C / minute	
Ambient temperature during storage/transportation		
• min.	-40 °C	
• max.	70 °C	
Air pressure acc. to IEC 60068-2-13		
• Operation, min.	540 hPa	
• Operation, max.	1 140 hPa	
• Storage/transport, min.	540 hPa	
• Storage/transport, max.	1 140 hPa	
Altitude during operation relating to sea level		
• Installation altitude, min.	-1 000 m	
• Installation altitude, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual	
Relative humidity		
• Operation at 25 °C without condensation, max.	95 %	
Vibrations		
• Vibration resistance during operation acc. to IEC 60068-2-6	3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz	
• Operation, tested according to IEC 60068-2-6	Yes	
Shock testing		
• tested according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms	
Pollutant concentrations		
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free	
Connection method		
required front connector	No	
Mechanics/material		
Enclosure material (front)		
• Plastic	Yes	
Dimensions		
Width	30 mm	
Height	125 mm	
Depth	100 mm	
Weights		
Weight, approx.	170 g	
Classifications		
	Version	Classification

eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



General Product Approval

EMV

For use in hazardous locations



[China RoHS](#)



[Miscellaneous](#)



For use in hazardous locations

Test Certificates

Maritime application



[CCC-Ex](#)

[CCC-Ex](#)

[Type Test Certificates/Test Report](#)



Maritime application

Environment



[NK / Nippon Kaiji Kyokai](#)



[KR \(Korean Register of Shipping\)](#)



Environment



last modified:

10/23/2025