SIEMENS

Data sheet 6AV6881-0AD56-3CA0

pipe adapter VESA 100/75, IP65, INOX, for Pro devices, including trapezoidal plate INOX IP65, scope of supply: 1 pipe adapter, 1 trapezoidal plate with 3 icotek cable sleeves for 6 mm lines

General information	
Product type designation	VESA 100/75 flange mount IP65
Installation type/mounting	
Mounting	VESA 100 mm / 75 mm with M6 thread
Mounting type	Support arm with VESA 100 mm or 75 mm
Degree and class of protection	
IP (at the front)	IP65
Standards, approvals, certificates	
Use in hazardous areas	
● ATEX Zone 2	No
● ATEX Zone 22	No
● ATEX as target device	No
● IECEx Zone 1	No
● IECEx Zone 11	No
● IECEx Zone 2	No
● IECEx Zone 22	No
● cULus Class I Zone 1	No
● cULus Class I Zone 2, Division 2	No
● cULus Class II Division 2	No
● FM Class I Division 2	No
● FM Class II Division 2	No
Marine approval	
● Germanischer Lloyd (GL)	No
● American Bureau of Shipping (ABS)	No
● Bureau Veritas (BV)	No
● Det Norske Veritas (DNV)	No
● Korean Register of Shipping (KRS)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (Class NK)	No
● Polski Rejestr Statkow (PRS)	No
● Chinese Classification Society (CCS)	No
● Marine approval as target device	No
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	No
Ambient temperature during operation	
● min.	0 °C
● max.	55 °C
Ambient temperature during storage/transportation	
● min.	-20 °C

Subject to change without notice
© Copyright Siemens

● max.	70 °C
Relative humidity	
● Operation, max.	90 %
● Condensation permissible	No
Mechanics/material	
Material	
● Stainless steel	Yes; Stainless steel V2A
Dimensions	
Width	135 mm; VESA 100/75 PRO INOX adapter
Height	120 mm; VESA 100/75 PRO INOX adapter
Depth	67.5 mm; VESA 100/75 PRO INOX adapter
Scope of supply	
Delivery quantity in pieces	2; 1x VESA INOX IP65 adapter and 1x INOX cable entry INOX IP65 with ICOTEK 3-fach cable entry 6 mm
Components included	Without additional accessories
Other	
Merchandise	Yes; VESA 100/75 PRO INOX adapter set IP65
Manufacturer name	QUERUM products UG
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany
Target devices	Not suitable for 19" 4:3 devices
Note:	Max. load 35 kg, for expandable support arm mounting

Classifications

	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

other

Miscellaneous

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW

last modified: 1/25/2024

Subject to change without notice
© Copyright Siemens