

LOGO! AM2 RTD EXPAN. MODULE, PU: DC 12/24V, 2AI, -50 ...
+200 DEGR/C PT100/1000 FOR LOGO! 8



Installation type/mounting

Mounting on 35 mm DIN rail, 2 spacing units wide

Supply voltage

Rated value (DC)

- 12 V DC Yes; 10.8 V DC to 28.8 V DC
- 24 V DC Yes; 10.8 V DC to 28.8 V DC

Analog inputs

Number of analog inputs 2; 2 or 3 wire connection

Input ranges

- Voltage No
- Current No
- Resistance thermometer Yes; For PT100/PT1000 sensors

Input ranges (rated values), voltages

- 0 to +10 V No

Input ranges (rated values), currents

- 0 to 20 mA No

Input ranges (rated values), resistance thermometer

- Pt 100 Yes

EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
Marine approval	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Dimensions	
Width	35.5 mm
Height	90 mm
Depth	58 mm
last modified:	05/23/2017