

LOGO! TD TEXTDISPLAY, 6 LINES, 3 BACKGROUND COLORS 2
ETHERNET PORTS ACCESSORIES, FOR LOGO! 8



General information

Suitability for use	Can be used with LOGO! 8 and higher
---------------------	-------------------------------------

Display

Design of display	FSTN
-------------------	------

Line display

- | | |
|---------------------------------|----|
| • Number of lines | 6 |
| • Number of characters per line | 20 |

Backlighting

- | | |
|------------------------|-----|
| • Type of backlighting | LED |
|------------------------|-----|

Control elements

Keyboard fonts

- | | |
|--------------------------------------|-----|
| • System keys | Yes |
| — Number of configurable system keys | 0 |
| • Numeric/alphabetical input | No |
| — alphanumeric keyboard | No |

Installation type/mounting

Wall mounting/direct mounting	No
-------------------------------	----

Supply voltage	
Type of supply voltage	AC/DC
Rated value (DC)	12 V; 12 V DC, 12/24 V AC/DC
Power loss	
Power loss, typ.	1.8 W; Typical
Digital inputs	
Number of digital inputs	0
Interfaces	
Number of RS 485 interfaces	0
Interrupts/diagnostics/status information	
Diagnostic functions	No
Degree and class of protection	
IP (at the front)	IP65
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
FM approval	Yes
KC approval	Yes
Marine approval	
• American Bureau of Shipping (ABS)	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Accessories	
belongs to product	LOGO!
Mechanics/material	
Design of housing	plastic
Dimensions	
Width	128.2 mm
Height	86 mm
Depth	38.7 mm
Overall depth	38.7 mm
Weights	
Weight, approx.	220 g
Scope of supply	
Delivery quantity in pieces	1

last modified:

05/23/2017